

GEN-PAC ECONOMY GENERATORS

		MODEL	T8G	T10G	T12G	T15G	T20G	T25G	
		List Price	\$11,280	\$12,008	\$13,356	\$13,971	\$13,701	\$15,195	
Power Capability	Prime	kVA (kilovolt-amperes)	8.8	10.6	12.1	15	20	25	
		kW (kilowatts)	7.0	8.5	9.7	12	16	20	
		1Ø Amp Ratings	120V	73	89	101	125	167*	208*
			240V	36	44	51	63	83*	104*
		3Ø Amp Ratings	208V	Not Available	Not Available	Not Available	Not Available	56	69
			220V					52	66
	240V		48					60	
	Standby	kVA (kilovolt-amperes)	9.9	12.9	14.6	17	24	30	
		kW (kilowatts)	7.9	10.3	11.7	14	19	24	
		1Ø Amp Ratings	120V	82	107	122	141	200*	250*
			240V	41	54	61	70	100*	125*
		3Ø Amp Ratings	208V	Not Available	Not Available	Not Available	Not Available	67	83
220V			63					79	
240V	58		72						
Max Motor Starting *	Hp	3	4	5	8	12	12		
	kW	2	3	4	6	9	9		
Diesel Engine Data	Manufacturer	Kubota	Kubota	Kubota	Kubota	Isuzu	Isuzu		
	Model	D905-EBG1	D1105-EBG1	D1305-EBG1	D1505-EBG1	4LE2PV01	4LE2PV01		
	Cylinders	3	3	3	3	4	4		
	Air Intake (aspiration)	Natural	Natural	Natural	Natural	Natural	Natural		
	Cooling System	Std Rad	Std Rad	Std Rad	Std Rad	Std Rad	Std Rad		
	Fuel Cons. @ Full Load - Gal/Hr	0.7	0.9	1.1	1.2	1.2	1.5		
	Run Time @ Full Load - Hrs	42	34	28	25	25	20		
	Unit Weight	Dry (lb)	1360	1403	1461	1466	1640	1654	
Full (lb)		1577	1620	1678	1685	1857	1871		

* maximum motor size is based on 35% voltage dip at 480 VAC 3 phase 60Hz with a code G motor

* single phase option required to get listed single phase amp ratings

GENERAL FEATURES FOR ALL TEREX POWER GEN PACS

Generator Type	Brushless, 4 Pole, Synchronous, Single Bearing, 1800 rpm, Class H Insulation
Voltage - 1 Phase	120, 240
Voltage - 3 Phase	208, 220, 240 (on T20G and T25G)
Convenience Receptacles	2 each 20 A GFCI Duplex - 1 each 30 A Twistlock - 1 each 50 A Tempower
Voltage Regulation	Automatic Voltage Regulator ± 1 ½ % on all units
Speed Regulation	Mechanical Governor (+/- 5%)
Engine Protection	Low Oil Pressure and High Water Temp Shutdown
Fuel Capacity	30 Gallons - Additional 20 Gallon Available
Trailer Specs	3500# Spring Axle with 15" Wheels
Trailer Options	Pintle Ring Hitch, 2" Ball Hitch, Tail Lights, Braking Options
Dimensions (L x W x H)	121" x 63" x 53" Trailer Mounted