

# RL 4000 FLOODLIGHT SYSTEM

# TEREX POWER



## Economical and Effective Jobsite Lighting

The Terex Power RL 4000 light tower provides cost-effective portable floodlighting for nighttime construction, mining, emergency and municipal work.

Check out these features:

- Dual self-braking winch design for fast and easy tower erection and extension.
- 30 ft (almost 10m) light height at full extension for excellent illumination at long distances.
- 360 degree tower rotation to provide pin-point light positioning at your work site.
- 4000 Watts of light - enough to illuminate 7-1/2 acres.
- Quiet 71 dBA sound levels at 23 feet (7m).
- Excellent fuel economy providing more than 60 hours of run time per tank of fuel.
- Maintenance-friendly electrical assemblies make troubleshooting, service and repair a breeze.
- 3 cylinder diesel engine powers a brushless self regulated type generator.
- Centerpoint lifting bracket and fork lift pockets make transport easy.
- Compact design allows up to 10 units per truck load.
- Engine protection includes high water temperature and low oil pressure shutdowns.
- Cabinet is protected with a durable, fade resistant, polyester powder coat finish.

Products shown may have optional equipment.

# RL 4000 FLOODLIGHT SYSTEM

# TEREX POWER



## Other performance-proven RL 4000 features

- In travel position Terex Power RL 4000 is only 54" (136 cm) wide, 167" (424 cm) long.
- Operation is simple with a basic, user-friendly control panel.
- Convenience receptacles include a 120V GFCI duplex and a 240V, 30A twistlock providing you with available power for your job site tools.

## Worldwide Distribution Network Provides Parts and Service

With a network of factory-trained distributors and dealers in many of the major markets around the world, Terex can provide parts and service assistance to help keep downtime at a minimum. Terex Power products also carry a full-year limited warranty on parts and labor.

### RL 4000 Specifications and Dimensions

Lighting system, type	Metal halide w/core and coil ballast
Wattage	4000 W
Initial lumens	440,000
Light coverage, acres	7-1/2
Tower height	30' (9.1 m)
Engine type & model	Kubota/D905
Generator type	4 pole, brushless and self regulated
Continuous rating	6,000 W
Fuel tank capacity	30 gal. (114 l)
Fuel consumption @ full load	.5 gph (1.9 lph)
Unit dBA at 23 feet	71 dBA
Overall length	167" (424 cm)
Overall width, travel position	54" (137 cm)
Overall height, travel position	56" (142 cm)
Total weight, no fuel	1800 lbs. (816 kg)



Equipment can be ordered to meet CE or CSA requirements.

We reserve the right to amend these specifications at any time without notice. The only warranty applicable is our standard written warranty applicable to the particular product and sale. We make no other warranty, expressed or implied.

For more information, product demonstration, or details on purchase, lease and rental plans, please contact your local Terex Power distributor.

# TEREX

P. O. Box 3147, Rock Hill, SC 29732 USA  
803-324-3011 • Fax: 803-366-1101  
1-800-433-3026

[www.terex.com](http://www.terex.com)  
[sales@terexlight.com](mailto:sales@terexlight.com)